

WINDOW AND DOOR FLASHING

TEKTON®

**150mm and
200mm wide rolls**

Protecto Sill System

The professional's flexible flashing tape system, for waterproofing window and door openings.



BRANZ Appraised
Appraisal No. 444 [2005]



Marshall
Waterproofing
Professional Solutions

15
YEAR
Warranty



**Professional
Builders Box**





Cut building wrap and staple to inside of opening.



Apply Protecto Tak Primer to all areas that will be taped.



Cut detail tape to 250mm. Remove backing paper and fit to corners.



Peel plastic film from surface of Detail Tape and fold onto face of opening.



Protecto Tak Primer/Adhesive

369gr aerosol.

A spray on primer/adhesive, coloured blue for easy identification.



Detail Tape

150mm x 15m rolls.

1mm thick conformable tape that can be stretched and moulded to any shape.



Detail Tape is required on all four corners of the opening. Press firmly into corners.



Cut Sill Tape 200mm long and apply to bottom of jambs and fold onto face of opening.



Cut Sill Tape to length, apply to sill and fold onto face of opening.



All tapes to be pressed firmly into place to maximise adhesion.

Protecto Sill

150mm and 200mm wide x 30m rolls.



Polyethylene backed asphalt adhesive membrane 0.5mm thick.



Head Flashing Tape

50mm wide x 30m rolls.

NB: Tapes are not UV stable and need to be covered within 4 weeks of installation.

benefits of Protecto Sill System

- BRANZ APPRAISED # 444 (2005)
- SLIMLINE TAPES THAT MAXIMISE OPENING SPACE FOR WINDOW INSTALLATION
- FLEXIBLE FLASHING TAPE MEETING E2 AND WANZ REQUIREMENTS
- ZERO WASTE AS TAPES CAN BE OVERLAPPED
- 15 YEAR WARRANTY
- PRIMERS ALLOW ADHESION TO MOST SUBSTRATES

please note:

- For best results use Protecto Sill System on BRANZ Appraised Tekton Building Wrap.
- Protecto Sill System must be installed over clean/dry surfaces.
- Replace Protecto Tak Primer/adhesive with #80 primer when using the Sill System over masonry or steel.
- Store tapes in boxes until ready to use. Keep tapes cool and dry.
- Do not install tapes if temperatures are below 5 degrees centigrade.
- In cooler conditions warm tapes before applying.
- The Protecto Sill System complies with the requirements of E2 AS1 third edition, June 2004 and WANZ WIS recommendations.
- The tapes have been tested to ICBO acceptance criteria AC148 and meet all requirements.
- When joining tapes, an overlap of 50mm is required.
- BRANZ Appraised # 444 (2005).

other professional solutions by Marshall Waterproofing

- Protecto Tape - Parapet and handrail protection, BRANZ Appraisal #450 (2005).
- Anti Fracture Membrane (AFM) - crack suppression and waterproofing for under tiles. Interior BRANZ Appraisal # 461 (2005). Exterior BRANZ Appraisal # 449 (2005).
- Protecto Wall - Tanking and below ground applications, BRANZ Appraisal # 517 (2006).
- Pro-Joist - Cantilevered deck joist protection, BRANZ Appraisal #497 (2006).
- Pro-Drain 8 - The protection board that creates a neutral pressure zone between the foundation wall and subsoil.
- Tekton House Wrap - Building wrap of the future, BRANZ Appraisal # 548 (2007).

Oct 2007