

SUPER-STICK BUILDING TAPE®



TAPE SIZES

75mm x 23m

150mm x 23m

230mm x 23m



BRANZ Appraised

Appraisal No.846 [2013]



No VOCs, HFCCs, or CFCs
No Off-Gassing
Non-Allergenic
No Toxicity



PROTECTO SUPER-STICK BUILDING TAPE® can help reduce air infiltration as recommended by the ENERGY STAR HOME SEALING guidelines.

Marshall Innovations SUPER-STICK Building Tape® is a high performance window and door flashing tape designed to be installed down to -5 deg°C. No more issues regarding adhesion in the cool of winter or heat of summer. No additional primers or mechanical fasteners required. SUPER-STICK Building Tape® utilizes a high tack pressure sensitive adhesive (PSA) combined with a high performance toughened film. It is a greener & cleaner building tape solution that contains No VOC's, HFCC's, nor CFC's. It is non-toxic and non-allergenic. No more issues with sealant compatibility at the design or installation stage.

Benefits of SUPER-STICK Building Tape®

- Can be installed in extremely cold conditions to -5 deg°C*.
- Adheres to damp surfaces.
- Easy to install peel-and-stick application.
- UV resistant for 90 days.
- Compatible with most sealants, check suitability with sealant manufacturer.
- Can be used with RAB systems – Plywood, fibre cement sheet.
- Split back liner for easy install.
- Can be installed in very hot conditions.
- Extremely high puncture resistance & Tensile strength.
- Residential & Commercial applications.
- Very thin & no build up & won't affect cavity battens or window installation.
- BRANZ Appraised # 846 (2013).
- Also forms part of The Tekton Weatherization System BRANZ # 621 (2008).

*Note: Protecto SUPER-STICK Tape® can be applied in extreme cold weather; however we do not recommend applying tapes below 0°C due to health and safety reasons.

* When applying over any waterproofing membrane check for compatibility.



FREEPHONE: 0800 776 9727
www.mwnz.com

